Description

The USB 2.0 Graphic Adapter allows you to connect an extra monitor to your desktop PC or laptop's USB port. The connected monitor can be configured to either clone your primary screen, or extend the Windows desktop allowing visibility of more applications at the same time.

The USB 2.0 Graphic Adapter driver used to control the extra screen uses very little computer resource and offers a vast array of screen resolutions and color depths. This ensures that there is little difference in performance between a directly connected screen and a screen connected through the USB 2.0 Graphic Adapter

The USB 2.0 Graphic Adapter supports up to six simultaneous displays, including widescreen displays, extending your desktop and your horizons. It operates at a high resolution of 1920x1200 / 2048x1152.

Office Use:

•View large spreadsheets across two screens with display continuity
•Multitask more effectively without overlapping windows
•Open attachments on one screen while reading the e-mail on the other
Mobile Use:
•Do multiple screen displays and presentations without bringing another computer
Graphic Use:
•Use second display for pallets/tools
Data Entry Use:
•Type documents on one screen while viewing reference material on the other
Wall Street:
•Use a notebook for viewing multiple screens
•View charts and live data at the same time
Entertainment:
•View videos/TV on one screen and your desktop on the other scre
•Easily connect additional monitors using a USB 2.0 Cable
•Enjoy resolutions of up to 1920x1200 at 32 bit color
•Allows for effortless multitasking
•Bus Powered - No external power supply needed
•Supports usage through powered KVMP's or USB hubs

Resolution Supports
640 x 480
800 x 600
1024 x 768
1280 x 960
1280 x 1024
1360 x 768
1366 x 768
1368 x 768
1400 x 1050
1440 x 900
1600 x 1200

1600 x 1050
1920 x 1080
1920 x 1200
2048 x 1152

Features

- **Display Modes:**
  - Can easily Mirror the main display
  - Extend left, right, above, or below
  - Can be rotated left, right, or upside-down
  - DVI , VGA and HDMI Support
- Maximum: 1920x1200 or 2048x1152 Digital (@60Hz 32-bit)
- USB 2.0 Powered - Ultra Low Power
- Lossless Compression
- CRT, LCD, Projector Displays
- Windows Vista Aero Support
- Windows XP and Vista 32bit Support
- Standard and Widescreen ratio aspects
- High-Performance DDR Memory
- Uses a virtual driver
- Stackable by design with a small footprint
- Completely silent operation
- Onboard power and status indicator LEDs

Requirements

- Available USB 2.0 Port
- **Operating System:**
  - Windows 2000 SP4
  - Windows XP SP2
  - Windows Vista 32/64Bit with Aero support
  - Windows 7 32Bit/64Bit

Package Content

- 1 x USB to DVI Adapter
- 1 x Quick Start Guide
- 1 x CD-ROM with User Guide and Installation Software
- 1 x USB 2.0 Cable
- 1 x DVI to VGA Adapter
- 1 x DVI to HDMI Adapter (Optional)